



**GreenEx**  
FIRE SUPPRESSION SOLUTIONS



**GreenEx MSATT-2**  
**GreenSol Activation PCB**



Datasheet  
Series  
Version  
Date

MSATT-2  
MSATTPCB  
2.01  
13-02-2020

## MSATT-2

The GreenEx MSATT-2 aerosol activation PCB is capable of controlling and igniting two GreenSol extinguishing generators.

The MSATT-2 is compatible with all major fire extinguishing release panels with a EN-54 or UL-864 listing and certification.

The MSATT box is designed to connect 1 to 2 GreenSol Extinguishing generators.


### Main Features

- Capable of managing up to 20 GreenSol extinguishing generators
- Compatible with all main extinguishing panels EN-54 part 1, 2 and 4.
- Compatible with all main extinguishing panels UL-864
- Small-Safe-Simple
- Cost Effective

### Mechanical Specifications


#### Dimensions

Width 60 mm  
Height 20 mm  
Length 60 mm



## MSATT-2

### Schematic Diagram



### Additional Note

The MSATT-2 can activate one or two GreenSol aerosol generators from the A50 up to the A1000. Using the MSATT-2 to activate a GreenSol A5000, you can only activate one unit with one MSATT-2.

The maximum MSATT-2 activation PCB in one line is restricted to 10 MSATT PCB's.

All fire extinguishing panels / release panels units on the market and compliant with the standard EN54 parts 1,2 and 4 as well as all UL-864 panels are suitable for use with GreenSol Aerosol Extinguishing Systems, provided they have a dedicated 24VDC  $\geq 1.35$  A, discharge output (RAC) and are controlled with a current of surveillance **not** exceeding 5 mA.



Phone (Toll Free): 1-844-233-7547

Email: [sales@ssiproducs.ca](mailto:sales@ssiproducs.ca)

[ssiproducs.ca](http://ssiproducs.ca)